STARPOWER

SEMICONDUCTOR **IGBT**

GD1000HFX170P2S

1700V/1000A 2 in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as wind power.


Features

- Low $V_{CE(sat)}$ Trench IGBT technology
- 10μs short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Maximum junction temperature 175°C
- Enlarged Diode for regenerative operation
- Isolated copper baseplate using DBC technology
- High power and thermal cycling capability

Typical Applications

- High Power Converter
- Wind Power
- Auxiliary Inverter

Equivalent Circuit Schematic



Absolute Maximum Ratings T_C=25°C unless otherwise noted

IGBT

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	1700	V
V_{GES}	Gate-Emitter Voltage	±20	V
I_C	Collector Current @ T_C=25°C @ T_C=100°C	1604 1000	A
I_{CM}	Pulsed Collector Current t_p=1ms	2000	A
P_D	Maximum Power Dissipation @ T_j=175°C	6.25	kW

Diode

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1700	V
I_F	Diode Continuous Forward Current	1000	A
I_{FM}	Diode Maximum Forward Current t_p=1ms	2000	A

Module

Symbol	Description	Value	Unit
T_{jmax}	Maximum Junction Temperature	175	°C
T_{jop}	Operating Junction Temperature	-40 to +150	°C
T_{STG}	Storage Temperature Range	-40 to +150	°C
V_{ISO}	Isolation Voltage RMS,f=50Hz,t=1min	4000	V

IGBT Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	I_C=1000A,V_{GE}=15V, T_j=25°C		1.95	2.40	V
		I_C=1000A,V_{GE}=15V, T_j=125°C		2.40		
		I_C=1000A,V_{GE}=15V, T_j=150°C		2.50		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	I_C=40.0mA,V_{CE}=V_{GE}, T_j=25°C	5.6	6.2	6.8	V
I_{CES}	Collector Cut-Off Current	V_{CE}=V_{CES},V_{GE}=0V, T_j=25°C			5.0	mA
I_{GES}	Gate-Emitter Leakage Current	V_{GE}=V_{GES},V_{CE}=0V, T_j=25°C			400	nA
R_{Gint}	Internal Gate Resistance			2.3		Ω
C_{ies}	Input Capacitance	V_{CE}=25V,f= 1MHz, V_{GE}=0V		108		nF
C_{res}	Reverse Transfer Capacitance			2.63		nF
Q_G	Gate Charge	V_{GE}=-15…+15V		9.43		μC
$t_{d(on)}$	Turn-On Delay Time	V_{CC}=900V,I_C=1000A, R_{Gon}=1.2Ω,R_{Goff}=1.8Ω V_{GE}=±15V,T_j=25°C		468		ns
t_r	Rise Time			95		ns
$t_{d(off)}$	Turn-Off Delay Time			850		ns
t_f	Fall Time			363		ns
E_{on}	Turn-On Switching Loss			292		mJ
E_{off}	Turn-Off Switching Loss			230		mJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC}=900V,I_C=1000A, R_{Gon}=1.2Ω,R_{Goff}=1.8Ω V_{GE}=±15V,T_j=125°C		480		ns
t_r	Rise Time			120		ns
$t_{d(off)}$	Turn-Off Delay Time			1031		ns
t_f	Fall Time			613		ns
E_{on}	Turn-On Switching Loss			439		mJ
E_{off}	Turn-Off Switching Loss			325		mJ
$t_{d(on)}$	Turn-On Delay Time	V_{CC}=900V,I_C=1000A, R_{Gon}=1.2Ω,R_{Goff}=1.8Ω V_{GE}=±15V,T_j=150°C		480		ns
t_r	Rise Time			120		ns
$t_{d(off)}$	Turn-Off Delay Time			1040		ns
t_f	Fall Time			708		ns
E_{on}	Turn-On Switching Loss			447		mJ
E_{off}	Turn-Off Switching Loss			347		mJ
I_{SC}	SC Data	t_P≤10μs,V_{GE}=15V, T_j=150°C,V_{CC}=1300V, V_{CEM}≤1700V		4000		A

Diode Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	I_F=1000A,V_{GE}=0V,T_j=25°C		1.85	2.30	V
		I_F=1000A,V_{GE}=0V,T_j=125°C		2.00		
		I_F=1000A,V_{GE}=0V,T_j=150°C		2.05		
Q_r	Recovered Charge	V_R=900V,I_F=1000A, -di/dt=9200A/µs,V_{GE}=-15V T_j=25°C		270		µC
I_{RM}	Peak Reverse Recovery Current			1155		A
E_{rec}	Reverse Recovery Energy			132		mJ
Q_r	Recovered Charge	V_R=900V,I_F=1000A, -di/dt=9200A/µs,V_{GE}=-15V T_j=125°C		451		µC
I_{RM}	Peak Reverse Recovery Current			1260		A
E_{rec}	Reverse Recovery Energy			241		mJ
Q_r	Recovered Charge	V_R=900V,I_F=1000A, -di/dt=9200A/µs,V_{GE}=-15V T_j=150°C		528		µC
I_{RM}	Peak Reverse Recovery Current			1250		A
E_{rec}	Reverse Recovery Energy			294		mJ

NTC Characteristics T^C=25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R_{25}	Rated Resistance			5.0		kΩ
ΔR/R	Deviation of R_{100}	T_C=100 °C,R_{100}=493.3Ω	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15K))]$		3375		K
$B_{25/80}$	B-value	$R_2=R_{25}\exp[B_{25/80}(1/T_2-1/(298.15K))]$		3411		K
$B_{25/100}$	B-value	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298.15K))]$		3433		K

Module Characteristics T_C=25°C unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
L_{CE}	Stray Inductance		10		nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.20		mΩ
R_{thJC}	Junction-to-Case (per IGBT) Junction-to-Case (per Diode)			24.0 48.0	K/kW
R_{thCH}	Case-to-Heatsink (per IGBT) Case-to-Heatsink (per Diode) Case-to-Heatsink (per Module)		9.0 18.0 3.0		K/kW
M	Terminal Connection Torque, Screw M4 Terminal Connection Torque, Screw M8 Mounting Torque, Screw M5	1.8 8.0 3.0		2.1 10 6.0	N.m
G	Weight of Module		1210		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs. I_C




Fig 4. IGBT Switching Loss vs. R_G




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs. I_F




Fig 9. Diode Switching Loss vs. R_G




Fig 10. Diode Transient Thermal Impedance






Fig 11. NTC Temperature Characteristic

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. A ny such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.